


Заклепка закрытого типа

Тип **5-ASF LF**

Увеличенный борт

Алюминиевый сплав (AlMg 5,0) / Углеродистая сталь



D, мм +0,08/-0,15	L, мм	Dk, мм	k, мм	d1, мм max	L1, мм min	Drill, мм	Grip, мм	H	H	Артикул
3,2	6,5	9,5 +0,3/-0,4	2,0	2,0	25	3,4	0,5-2,0	1050	1250	5-ASF LF 32065
	8,0						2,0-3,5			5-ASF LF 32080
	9,5						3,5-5,0			5-ASF LF 32095
	11,0						5,0-6,5			5-ASF LF 32110
	12,5						6,5-8,0			5-ASF LF 32125
4,0	8,0	12,0 +0,5/-1,0	2,2	2,5	27	4,1	0,5-3,5	1550	2150	5-ASF LF 40080
	9,5						3,5-5,0			5-ASF LF 40095
	11,0						5,0-6,5			5-ASF LF 40110
	12,5						6,5-8,0			5-ASF LF 40125
	15,0						8,0-12,5			5-ASF LF 40150
4,8	8,0	16,0 +0,5/-1,0	2,5	3,0	27	4,9	1,0-3,0	2200	3050	5-ASF LF 48080
	9,5						3,0-5,0			5-ASF LF 48095
	11,0						5,0-6,5			5-ASF LF 48110
	13,0						6,5-8,0			5-ASF LF 48130
	14,5						8,0-9,5			5-ASF LF 48145
	16,0						9,5-11,0			5-ASF LF 48160
	18,0						11,0-13,0			5-ASF LF 48180
	21,0						13,0-16,0			5-ASF LF 48210
25,0	16,0-20,0	5-ASF LF 48250								
6,4	12,5	16,0 +0,5/-1,0	3,2	3,9	27	6,5	1,5-6,0	4000	4900	5-ASF LF 64125
	16,0						6,0-8,5			5-ASF LF 64160
	18,0						8,5-10,5			5-ASF LF 64180
	20,0						10,5-12,5			5-ASF LF 64200
	25,0						12,5-17,5			5-ASF LF 64250