


Заклепка рифленая
Тип ASG
Стандартный борт
Алюминиевый сплав / Углеродистая сталь



D, мм +0,08/-0,15	L, мм	Dk, мм	d1, мм max	L1, мм min	Depth, мм	Drill, мм	Grip, мм			Артикул
3,2	10,0	6,4 +0/-0,6	1,3	25	14,0	3,6	6,0	600	980	ASG 3210
	12,0				16,0		8,0			ASG 3212
	14,0				18,0		10,0			ASG 3214
4,0	8,0	8,0 +0/-1,0	1,7	27	13,0	4,4	4,0	900	1350	ASG 4008
	10,0				15,0		6,0			ASG 4010
	12,0				17,0		8,0			ASG 4012
	14,0				19,0		10,0			ASG 4014
	16,0				21,0		12,0			ASG 4016
	18,0				23,0		14,0			ASG 4018
4,8	8,0	9,5 +0/-1,0	2,0	27	14,0	5,3	4,0	1350	1880	ASG 4808
	10,0				16,0		6,0			ASG 4810
	12,0				18,0		8,0			ASG 4812
	14,0				20,0		10,0			ASG 4814
	16,0				22,0		12,0			ASG 4816
	18,0				24,0		14,0			ASG 4818
	20,0				26,0		16,0			ASG 4820
25,0	31,0	21,0	ASG 4825							
30,0	36,0	26,0	ASG 4830							